

## TR360 Machine Control Receiver

### Feature:

- Length of receiving windows 25 cm,360°reception range
- Working with construction machine for permanent level control.
- Detects beam from rotating laser levels of any brand
- Water and dust protected metal housing according to IP 66
- Remote display
- TR360M-with strong magnets
- TR360C- with screw clamp

### Specification:

*Accuracy fine:	±3mm to ±12mm
*Accuracy coarse:	±5mm to ±25mm
*Rechargeable batteries:	7.2V NiMH/2500 mAh
*Operating time:	40h
*Charging time:	10h
*Operating temperature:	-20°C to +50°C
*Size:	376 x 180 x 60 mm
*Weight:	3.1kg



TR360M-with strong magnets



TR360C-with screw clamp

## MDL60 Digital level

### Features:

- \*Backlit LCD display
- \*Measure angles in degrees, percentages, Alternate zero mode.
- \*Slope display
- \*Acoustic signal at level and plumb
- \*Self-checking accuracy.
- \*Self-calibration
- \*Auto power-off.

### Specification:

Working range:	360° quadrants
Resolution:	0.1°
Accuracy:	±0.1°
Power:	9v Alkaline battery.
Auto power off:	5 minutes
Battery life:	50 hours
Operating temperature:	-5°C-+40°C
Dimension:	600x25x50mm
Weight:	600g



**SHANGHAI MERRYPAL IMPORT & EXPORT CO.,LTD**

RM D5 9F, JIANGSU MANSION, 528 LAOSHAN ROAD,  
SHANGHAI,200122,P.R.CHINA

TEL:86-21-50819935,50819936 FAX:86-21-50819938

E-mail:chinasurveying@yahoo.com WEBSITE:www.oriensurveying.com